Specialist Geomembranes

Technical Data Sheet

Landflex™ REP115 Scrim Reinforced EPDM



Versatile, highly flexible and suitable for a number of applications including:

- Waterproof tank linings
- Water features, reservoirs, lakes, lagoons
- Canals & rivers
- Fire suppression & pumping systems
- Heavy duty water storage bladders

The information herein is based upon data obtained by the manufacturer and is considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data. This information is furnished upon the condition that the person receiving it shall evaluate its suitability for the specific application.

Material Properties	Unit	Test Method	Typical Values
Thickness	mm	-	1.15
Width	mm		1700
Roll length	-		As required
Tensile strength	N/50mm	BS EN ISO 1421	Warp 550 Weft 550
Elongation at break	%	BS EN ISO 1421	Warp 20 Weft 20
Weight	g/m²	-	1416
Burst strength	kN/m²	BS EN 12332	1250

Example application:
Waterproof tank liners





BUTEK Tanks
BUTEK Landline

Specialist divisions of Butyl Products Ltd
T: +44 (0) 1277 653 281
E: enquiries@butektanks.co.uk W: butektanks.com
E: enquiries@butek-landline.co.uk W: buteklandline.co.uk